



SPECIFICATION FOR APPROVAL

www.twktec.com

KSA-90W-120750M2

AC/DC ADAPTOR

AC/DC ADAPTOR

KSA-90W-120750M2 Manufacturer Part No.: KS250247

KTEC

Customer NameKTEC

Customer Part NO.

Project Modify List

Item	Content	Rev.	Date	Prepared By	Checked By
1	First REV.	A	2025-11-18	Liao xiaoyan	Wu qingxiong

Manufacturer

SALES	QE	APPROVED BY	MADE BY
Tai	徐海鑫	贺洪明	冯朵朵

Approved Signatures

APPROVED BY

CHECKED BY

TESTED BY

AC/DC ADAPTOR

KSA-90W-120750M2 Manufacturer Part No.: KS250247



1.	INPUT REQUIREMENTS	4
1.1	Highlight & Features.....	4
1.2	General Description.....	4
1.3	Chemical Substance Control Laws	4
1.4	Input Conditions	4
1.5	Ac inrush current	4
2.	OUTPUT REQUIREMENTS	5
3.	MECHANICAL.....	6
3.1	Enclosure and Layout	6
3.2	Input and Output Configuration	6
4.	REGULATORY COMPLIANCE	7
4.1	EMC Specifications.....	7
4.1.1	Radiated and Conducted Emission.....	7
4.2	Immunity.....	7
4.2.1	Electrostatic Discharge Immunity.....	7
4.2.2	Radiated Field Immunity	7
4.2.3	Fast Transient Immunity	7
4.2.4	Surge Immunity	7
4.3	Safety Requirements and Certification.....	8
4.3.1	Regulatory Standard	8
4.3.2	Additional Safety Requirements	8
5.	ENVIRONMENTAL REQUIREMENTS	8
6.	APPEARANCE DRAWING: (UNIT: MM)	9
7.	NAME PLATE	10
8.	DIMENSION OF OUTPUT PLUG & DC CORD (UNIT: MM)	11
9.	PACKING (UNIT: MM)	12

AC/DC ADAPTOR

KSA-90W-120750M2 Manufacturer Part No.: KS250247



1. INPUT REQUIREMENTS

1.1 Highlight & Features

- Simple design philosophy.
- Reliability level of 50K hours MTBF @ 25°C (rated input voltage and using the Telcordia SR-332 issue 3 method).
- DC output voltage must be Safe Extra Low Voltage (SELV) & Limited Power as defined by IEC62368-1.
- Cooling: natural convection

1.2 General Description

This specification defines the performance characteristics for a class II adapter, single-phase 90.0 watts.
Single output level power supply.

1.3 Chemical Substance Control Laws

PAHS 6P NP NOP REACH ROHS

1.4 Input Conditions

The supply shall operate over the voltage ranges as follows :

Rated input voltage	100-240Vac
Operating range	90-264Vac
Rated input frequency	50/60Hz +/- 3Hz
Rated input current	1.3A Max.
Power consumption	0.15W Max. (no-loading)
Primary current protection	An adequate internal fuse on the AC input line is provided.
Input Configuration	<u>2</u> Conductor

1.5 Ac inrush current

No damage shall be occurred and the input fuse shall not be blown up nominal input voltage full load, 25°C cold start.

AC/DC ADAPTOR

KSA-90W-120750M2 Manufacturer Part No.: KS250247



2. OUTPUT REQUIREMENTS

2.1	Nominal DC output voltage	+12.0V
2.2	Minimum load current	0.05A
2.3	Rating load current	7.5A
2.4	Peak load current	/
2.5	Rating output power	90.0W
2.6	Line regulation	The line regulation is less than $\pm 5\%$ while measuring at rated load and $\pm 10\%$ of input voltage changing.
2.7	Load regulation	The load regulation for +12.0V is less than $\pm 5\%$, at measured output load from 10% to 100% rated load.
2.8	Ripple and noise	150 mVp-p
		Add 0.1uF/50V ceramic capacitor and 10uF/50V aluminum electrolytic capacitor across the output terminal. Measured with 20MHz Bandwidth Oscilloscope.
2.9	Average efficiency	89% minimum. 115V/60Hz and 230V/50Hz, output current from 100%, 75%, 50%, 25%
2.10	Turn on delay time	3000 ms max. at nominal input AC voltage and full load.
2.11	Rise time	The supply shall have a start-up rise time of less than 40ms to rise to within regulation limits for all DC outputs.
2.12	Hold up time	8 ms minimum at nominal input 100Vac minimum voltage and full load.
2.13	Output over-shoot	Less than 10% of nominal voltage value.
2.14	LED indication function	Green LED
2.15	Protection function	
	Over-voltage protection	The output voltage shall be clamped by internal protection.
	Short-circuit protection	The adapter shall not damage and with auto recovery function by short the DC output to Ground.
	Over current protection	The power supply will be protection when output power at 105-180% of all rated DC output.

AC/DC ADAPTOR

KSA-90W-120750M2 Manufacturer Part No.: KS250247



3. MECHANICAL

3.1 Enclosure and Layout

Plastic case	UL94V-0
Weight	/ g (Max.)
Dimensions	146.0*64.0*34.5mm
Color	Black

3.2 Input and Output Configuration

Input pin	Mini 2PIN
Output connector	DC plug type: 5.5*2.1*10 mm(Fork and groove)
Polarity	Center “+”
Cable	1.5M VW-1 80℃ 300V 1185 4.0Q 16AWG BLACK

AC/DC ADAPTOR

KSA-90W-120750M2 Manufacturer Part No.: KS250247



4. REGULATORY COMPLIANCE

4.1 EMC Specifications

The external power supply must meet all specification in this section. it is required that the external power supply work closely with the customer's equipment in order to get the best EMC solution.

4.1.1 Radiated and Conducted Emission

FCC part 15: Class B for radiated and conducted emissions.

EN55032, Class B for radiated and conducted emissions.

4.2 Immunity

4.2.1 Electrostatic Discharge Immunity

EN 55035, EN 61000-4-2

Air Discharge: $\pm 8\text{kv}$

Contact Discharge: $\pm 4\text{kv}$

Performance Criteria B

Electrostatic-discharge test by contact or air should be conducted with Static-discharge tester (energy storage capacitance of 150pF and discharge resistance of 330 Ω) 8kv air discharge, 4kv contact discharge.

4.2.2 Radiated Field Immunity

EN 55035, EN 61000-4-3

Frequency Range: 80-1000MHz, still need test singly 1800MHz, 2600MHz, 3500MHz, 5000MHz

Field Strength: 3V/m with 80% amplitude modulation of 1kHz

Performance Criteria A

Radio-frequency electromagnetic field susceptibility test, RS 80-1000MHz, 3V/m, 80%AM(1KHz).

4.2.3 Fast Transient Immunity

EN 55035, EN 61000-4-4

Power line: 1kv

Signal line: 0.5kv

Performance Criteria B

4.2.4 Surge Immunity

EN 55035, EN 61000-4-5

- Line to line: $\pm 1\text{kv}$

- Line to earth: $\pm 2\text{kv}$

- + 90°/ -270°

AC/DC ADAPTOR

KSA-90W-120750M2 Manufacturer Part No.: KS250247

KTEC

Lighting surge voltage of differential and common modes shall be applies across AC input lines and across input and frame ground.

4.3 Safety Requirements and Certification

4.3.1 Regulatory Standard

The power supply shall comply with the following international regulatory standards:

For short	Country or Region	Certified Status	Standard
UL	USA	/	UL 62368-1
CUL	Canada	/	CSA C22.2 NO.62368-1
CE	Europe	/	EN 62368-1

4.3.2 Additional Safety Requirements

- Ⓒ Dielectric Withstand Voltage, Primary(input AC short)-to-Secondary(output DC short): 3000 Vac, 5mA, 1 minute.
- Ⓒ Insulation Resistance, Input to output: 10M Ω(MIN.) at 500 VDC.
- Ⓒ Reinforced insulation system, Primary-to-Ground and Primary-to-Secondary.
- Ⓒ The leakage current shall not exceed 0.25mA.

5. ENVIRONMENTAL REQUIREMENTS


Temperature	Operating	0 °C +40 °C
	Non-Operating	-20 °C +80 °C
Humidity	Operating	10%~90% (Non Condensing)
	Non-Operating	10%~90% (Non Condensing)
Altitude	Sea level to 5000m	

AC/DC ADAPTOR

KSA-90W-120750M2 Manufacturer Part No.: KS250247

KTEC

6. APPEARANCE DRAWING: (UNIT: MM)





NOTE:

1. Case cover & chassis material PC BLACK (NO KTEC)
2. AC PIN MATERIAL: BRASS (NI PLATED)
3. PAHS 6P NP NOP REACH ROHS
4. Satin Finish
5. Top mold: MSC025005; Bottom mold: MSC025006

AC/DC ADAPTOR

KSA-90W-120750M2 Manufacturer Part No.: KS250247

7. NAME PLATE



Note: Laser

PXXYY (P=PAHS, 6P, NP XX=Week, YY=Year), use the actual production date.

SN (Data Matrix Code size: 5*5mm):

First code G (Ktec) + Production part number (Product code)+ Ten yards of flow code SSSSSSSSSS (decimal) Total 19 codes


Example : GKS2502470000000001, GKS2502470000000002...GKS2502479999999999.

AC/DC ADAPTOR

KSA-90W-120750M2 Manufacturer Part No.: KS250247



8. DIMENSION OF OUTPUT PLUG & DC CORD (UNIT: MM)



NOTE: (unit:mm)

- 1). WIRE TYPE: 1185 4.0Ø VW-1 80°C 300V L=1500mm 16AWG BLACK
- 2). THE POLARITY:
- 3). PAHS 6P NP NOP REACH RoHS
- 4). SR Mold: ML00512

AC/DC ADAPTOR

KSA-90W-120750M2 Manufacturer Part No.: KS250247

KTEC

9. PACKING (UNIT: MM)

