



SPECIFICATION FOR APPROVAL

www.twktec.com

KSA-48C-120400VE-1

AC/DC ADAPTOR

Customer Part NO.

[illegible]

SALES	QE	APPROVED BY	MADE BY
Frank	徐海鑫	贺洪明	冯朵朵

TESTED BY

--	--	--

AC/DC ADAPTOR

KSA-48C-120400VE-1 Manufacturer Part No.: KS250243



1.	INPUT REQUIREMENTS	4
1.1	Highlight & Features.....	4
1.2	General Description.....	4
1.3	Chemical Substance Control Laws	4
1.4	Input Conditions	4
1.5	Ac inrush current	4
2.	OUTPUT REQUIREMENTS	5
3.	MECHANICAL.....	6
3.1	Enclosure and Layout	6
3.2	Input and Output Configuration	6
4.	REGULATORY COMPLIANCE	7
4.1	EMC Specifications.....	7
4.1.1	Radiated and Conducted Emission.....	7
4.1.2	Harmonics	7
4.1.3	Voltage fluctuations and Flicker	7
4.2	Immunity.....	7
4.2.1	Electrostatic Discharge Immunity.....	7
4.2.2	Radiated Field Immunity	7
4.2.3	Fast Transient Immunity	7
4.2.4	Surge Immunity	8
4.2.5	Conducted Field Immunity.....	8
4.2.6	Voltage dips/short interruptions	8
4.2.7	Electromagnetic compatibility	8
4.3	Safety Requirements and Certification.....	9
4.3.1	Regulatory Standard	9
4.3.2	Additional Safety Requirements	9
4.4	RoHS directive.....	9
4.5	ESPR regulation	9
5.	ENVIRONMENTAL REQUIREMENTS	9
6.	APPEARANCE DRAWING: (UNIT: MM)	10
7.	NAME PLATE	11
8.	DIMENSION OF OUTPUT PLUG & DC CORD (UNIT: MM)	12
9.	PACKING (UNIT: MM)	13

AC/DC ADAPTOR

KSA-48C-120400VE-1 Manufacturer Part No.: KS250243



1. INPUT REQUIREMENTS

1.1 Highlight & Features

- Simple design philosophy
- MTBF: The MTBF shall be at least 300,000 hours at 25°C, full load, 230Vac/50Hz input, following SR-332 issue 03(2011)
- Electrolytic capacitor life time : The life time of Electrolytic Capacitor should be greater than 3 years under 230Vac/50Hz input @35°C ambient condition with 90% load.
- Continuous operational lifetime >7 years at 25°C ambient with 230Vac full load.
- DC output voltage must be Safe Extra Low Voltage (SELV) & Limited Power as defined by IEC62368-1.
- Cooling: natural convection.
- No Y Cap

1.2 General Description

This specification defines the performance characteristics for a class II adapter, single-phase 48.0 watts. Single output level power supply.

1.3 Chemical Substance Control Laws

PAHS, 6P, NP, REACH, NOP, ROHS, HF, SCIP FREE

1.4 Input Conditions

The supply shall operate over the voltage ranges as follows:

Rated input voltage	200-240Vac
Operating range	180-264Vac
Rated input frequency	50/60Hz +/- 3Hz
Rated input current	1.2A maximum
Power consumption(no-loading)	0.075W max.@230Vac
Primary current protection	An adequate internal fuse on the AC input line is provided.
Input Configuration	<u>2</u> Conductor

1.5 Ac inrush current

No damage shall be occurred and the input fuse shall not be blown up nominal input voltage full load 25°C cold start.

AC/DC ADAPTOR

KSA-48C-120400VE-1 Manufacturer Part No.: KS250243



2. OUTPUT REQUIREMENTS

2.1	Nominal DC output voltage	+12.0V
2.2	Minimum load current	0.0A
2.3	Rating load current	4.0A
2.4	Peak load current	/
2.5	Rating output power	48.0W
2.6	Line regulation	The line regulation is less than $\pm 5\%$ while measuring at rated load and $\pm 10\%$ of input voltage changing.
2.7	Load regulation	The load regulation for +12.0V is less than $\pm 5\%$, at measured output load from 10% to 100% rated load.
2.8	Ripple and noise	150mVp-p Add 0.1uF/50V ceramic capacitor and 10uF/50V aluminum electrolytic capacitor across the output terminal. Measured with 20MHz Bandwidth Oscilloscope.
2.10	Average efficiency	90.00% minimum (output current from 100%, 75%, 50%, 25%). 80.00% minimum 10% load. No load: $\leq 0.075W$ Test conditions: 230V/50Hz. Test procedures: EN 50563:2011 & EN 50564:2011 Meet ErP VI & COC V5 Tier 2 Regulation (EU)2019/1782
2.11	Turn on delay time	3000ms maximum at nominal input AC voltage and full load.
2.12	Rise time	The supply shall have a start-up rise time of less than 20ms to rise to within regulation limits for all DC outputs.
2.13	Hold up time	8ms minimum at 200Vac and full load.
2.14	Output over-shoot	Less than 10% of nominal voltage value.
2.15	LED indication function	/
2.16	Protection function	
2.16.1	Over-voltage protection	The output voltage shall be clamped by internal protection.
2.16.2	Short-circuit protection	The adapter shall not be damaged by short the DC output to Ground. The adapter shall resume normal operation when a short circuited fault condition is removed.
2.16.3	Over current protection	The output shall be protected against the over current conditions.

AC/DC ADAPTOR

KSA-48C-120400VE-1 Manufacturer Part No.: KS250243



3. MECHANICAL

3.1 Enclosure and Layout

Plastic case	UL94V-0
Weight	210g (Max.)
Dimensions	89x34x45mm
Color	WHITE(WT-07)

3.2 Input and Output Configuration

Input pin	EU Pin
Output connector	DC plug type: 4.75*1.7*9.5mm (Fork and Groove)
Polarity	Center “+”
Cable	1.5M VW-1 80°C 300V UL10800 16AWG 4.0Q WHITE(WT-07)

AC/DC ADAPTOR

KSA-48C-120400VE-1 Manufacturer Part No.: KS250243



4. REGULATORY COMPLIANCE

4.1 EMC Specifications

The external power supply must meet all specification in this section. it is required that the external power supply work closely with the customer's equipment in order to get the best EMC solution.

4.1.1 Radiated and Conducted Emission

FCC part 15: Class B for radiated and conducted emissions.

EN55032, Class B for radiated and conducted emissions.

4.1.2 Harmonics

Meet EN61000-3-2

4.1.3 Voltage fluctuations and Flicker

Meet EN61000-3-3

4.2 Immunity

4.2.1 Electrostatic Discharge Immunity

EN 55035, EN 61000-4-2

Air Discharge: $\pm 8\text{kv}$

Contact Discharge: $\pm 4\text{kv}$

Performance Criteria B

Electrostatic-discharge test by contact or air should be conducted with Static-discharge tester (energy storage capacitance of 150pF and discharge resistance of 330 Ω) 8kv air discharge, 4kv contact discharge.

4.2.2 Radiated Field Immunity

EN 55035, EN 61000-4-3

Frequency Range: 80-1000MHz, still need test singly 1800MHz, 2600MHz, 3500MHz, 5000MHz

Field Strength: 3V/m with 80% amplitude modulation of 1kHz Performance Criteria A

Radio-frequency electromagnetic field susceptibility test, RS 80-1000MHz, 3V/m, 80%AM(1KHz).

4.2.3 Fast Transient Immunity

EN 55035, EN 61000-4-4

Power line: 1kv

Performance Criteria B

AC/DC ADAPTOR

KSA-48C-120400VE-1 Manufacturer Part No.: KS250243



4.2.4 Surge Immunity

ITU-T K.21

Differential mode : Line to line: $\pm 6\text{kv}$

Common mode : Line to earth: $\pm 6\text{kv}$ (L1-GND;L2-GND;L1/L2-GND)

Surge pulse: 1.2 microseconds / 50 microseconds.

Test number of times: 5 times (cycle: 1 minute)

Lightning surge voltage shall be applied in differential and common mode to AC input lines and cross primary AC input and secondary GND.

4.2.5 Conducted Field Immunity

EN 55035, EN 61000-4-6

Frequency Range: 0.15-80MHz(0,15 to 10 MHz , 3V ; 10 to 30 MHz , 3-1V ; 30 to 80 MHz , 1V)

Field Strength: 3A/m with 80% amplitude modulation of 1KHz

Performance Criteria A

4.2.6 Voltage dips/short interruptions

EN 55035, EN 61000-4-11

30% reduction, 0.5 periods, Criteria A,30%

reduction, 25 periods, Criteria B,60%

reduction, 5 periods, Criteria B

50Hz/60Hz

0%U T * for 0.5per

0%U T * for 250/300per

70%U T * for25/30per

4.2.7 Electromagnetic compatibility

EN55035, EN 61000-4-8

Frequency Range: 50Hz

Field Strength: 1A/m

Observation Time: 1 minute

Inductance Coil: Rectangular type, 1mx1m

Performance Criteria A

AC/DC ADAPTOR

KSA-48C-120400VE-1 Manufacturer Part No.: KS250243

KTEC

4.3 Safety Requirements and Certification

4.3.1 Regulatory Standard

The power supply shall comply with the following international regulatory standards:

for short	Country or Region	Certified Status	Standard
CE-EMC	Europe	Meet	EN 55032+EN55035
CE-LVD	Europe	Meet	EN62368-1

4.3.2 Additional Safety Requirements

- ◎ Dielectric Withstand Voltage, Primary(input AC short)-to-Secondary(output DC short): 3000Vac, 10mA, 1minute.
- ◎ Insulation Resistance, Input to output: 50MΩ (MIN.) at 500 VDC.
- ◎ Reinforced insulation system, Primary-to-Ground and Primary-to-Secondary.
- ◎ The leakage current shall not exceed 0.25mA.

4.4 RoHS directive

This product must comply with: EU Directive 2011/65/EU for Restriction of Hazardous Substance (RoHS)

4.5 ESPR regulation

This product must comply with Regulation (EU)2024/1781(ESPR)

5. ENVIRONMENTAL REQUIREMENTS


Temperature	Operating	0°C +45°C
	Non-Operating	-20°C +55°C
Humidity	Operating	10%~90% (Non Condensing)
	Non-Operating	5%~95% (Non Condensing)
Altitude	Sea level to 5000m	

AC/DC ADAPTOR

KSA-48C-120400VE-1 Manufacturer Part No.: KS250243



6. APPEARANCE DRAWING: (UNIT: MM)



NOTE: 1. Case cover & chassis material:

PCR 98% WHITE(WT-07) (NO KTEC)

2. AC PIN MATERIAL: BRASS (NI PLATED)

3. PAHS, 6P, NP, REACH, ROHS, NOP, HF, SCIP FREE

4. Satin finish: nameplate area has VDI 21 very fine texture.

Rest of PSU has texture VDI 3400 Ref.33


5. Top mold: MSC025002 Bottom mold: MSC025001

AC/DC ADAPTOR

KSA-48C-120400VE-1 Manufacturer Part No.: KS250243



7. NAME PLATE




Note: Laser
QR code: 7.0*7.0mm HXXYY (HXXYY: H=HF XX=WEEK YY=YEAR),按实际生产日期
Laser Color: Cool Gray 2C

AC/DC ADAPTOR

KSA-48C-120400VE-1 Manufacturer Part No.: KS250243




8. DIMENSION OF OUTPUT PLUG & DC CORD (UNIT: MM)



NOTE: (unit:mm)

- 1).WIRE TYPE:VW-1 80°C 300V L=1500mm UL10800 4.0Q 16AWG WHITE(WT-07)
- 2).THE POLARITY:
- 3).PAHS, 6P, NP, REACH, ROHS, NOP, HF, SCIP FREE
- 4).SR MOLD: ML00516



Magic Tape on the DC cable is moveable

